

TECHNICAL DATA SHEET (TDS)

Cam Cila

DESCRIPTION: Urathane alkyd based, single component, colorless and glossy parquet varnish.

CHARACTERISTIC: -High resistant against scratchs and corrosion, -Flexible and tough. -Durable against alcohol, grease and detergent on the surface.

APPLICATIO SURFACES: Can be used on all kinds of wooden parts and parquet coatings.

TECHNICAL INFORMATION:

Structure: Urethane alkyd

Class 1 Long Fat Vernier

Consumption: 10-14 (m² / lt), 85-138 (g / m²)

Thinning ratio: 10-15%

Application tools: Brush, Roller, Pistol.

Drying: Dust repulsive 2-4 hours; Full drying 7-8 hours; 72 hours to physical and chemical drying

Viscosity: 80 KU ± 5 (23 ° C)

Density: 0.92 ± 0.02 (g / ml)

Amount of solid matter: (55 ± 2)%

Dry film thickness: 30 ± 5

Wet film thickness: 60 ± 5

APPLICATION: The surfaces to be applied with Parquet Varnish should be cleaned with dirt and oil and primed with Cellulosic Filler Varnish after preparing a dry and clean surface. The gaps between the parquets should be filled with parquet varnish + Zimpara Stone paste made. Ready-to-use. If necessary, dilute with synthetic thinner and apply 2-3 times with brush. 8-12 hours should be waited between coats.



TECHNICAL DATA SHEET (TDS)

CAUTION:

R10 Flammable.

R51 / 53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapors may cause drowsiness and dizziness.

S2 Keep out of reach of children.

S16 Keep away from sources of ignition – No smoking.

S24 / 25 Avoid contact with eyes and skin.

S37 Wear suitable gloves.

S51 Use only in well-ventilated areas.

S57 Use a suitable container to avoid contamination.

S60 Dispose of this material and its container as hazardous waste.

S61 Avoid release to the environment. Refer to Special Instructions for Use / Safety Data Sheet.

S62 If swallowed, do not induce vomiting. Contact the first aid service immediately and show the container or label.

STORAGE: Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

PACKAGING: 15 lt, 2,5 lt, 0.75 lt tin Bucket.