

Class Tavan

DESCRIPTION: : Acrylic Copolymer Emulsion based, extra matt, roller or brush that leaves no traces, economical ceiling Primer.

CHARACTERISTIC :

-Breathable

-High covering and adhesiveness ability.

-Easily applicable.

-White colored and economical.

-Can be easily applied and leave no brush marks.

-Due to its water-based structure, it does not have an unpleasant sent.

APPLICATION SURFACES: Can be applied on all prepared ceiling surfaces.

TECHNICAL INFORMATION:

Structure: Stirene Acrylic

Consumption: 6-10 (m²/ lt), 100-150 (g/m²)

Thinning Ratio: 10-15 %

Recommended Primer: Silkcoat Universal Primer, Silkcoat İzolac

Recommended Putty: Silkcoat Acrylic Putty.

Application tools: Brush, Roller.

Drying: After 2 hours.

Viscosity: 120 KU \pm 10 (23 ° C)

pH: 8 – 9

Density: 1,75 \pm 0,05 (g / ml)

Amount of solid: (63 \pm 2) %

Thickness of dry coat: (50 \pm 5) micron

Thickness of wet coat: (95 \pm 5) micron

APPLICATION: The application surface should be free from all kinds of dust, dirt and oil. A clean, dry and solid surface should be obtained after lightly smoothing the blistered and old painted surfaces. If necessary, defects and cracks on the surface should be repaired with Silkcoat Internal Acrylic Putty. Silkcoat Class Ceiling is applied on new and absorbent surfaces after having applied Silkcoat İzolac. Silkcoat Class Ceiling is diluted with 10-15% of clean water and applied in two layers by roller, brush or spray method. Wait at least 2 hours between coats depending on the air temperature. The paint should be mixed until it is completely homogenous before use. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying.

CAUTION:

S2: Keep out of the reach of children.

S24 / 25: Avoid contact with eyes and skin.

S46: If swallowed, seek medical advice immediately; Show the container or label.

Store the product in a tightly closed container.

Do not pour into the sewer.

STORAGE: Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

PACKAGING: 25 Kg, 17.5 Kg, 10Kg, 3 Kg PE Bucket.