

Elasticoat Desenli

DESCRIPTION: Acrylic copolymer binder based matt exterior elastic coating.

CHARACTERISTIC: Elasticoat Pattern, which is quite different from the classical paints thanks to its specially formulated structure, is a combination of quality and aesthetics and it is applied by roller. Thanks to its superior elastomeric structure, it is an exterior coating covering the cracks in the bath. In addition to providing excellent decorative appearance on the facades, it has high resistance against external factors such as snow, rain, humidity, industrial effects and sun rays.

APPLICATION SURFACES: Can be applied on surfaces such as gross concrete, concrete, gypsum plaster, gypsum board, prefabricated concrete and similar building elements.

TECHNICAL INFORMATION:

Structure: Stirene acrylic

Consumption: 800- 1100 gr/m²

Thinner: Water

Thinning Ratio: No thinning, ready-to-use.

Density: 1,60 ± 0,05 (g / ml)

Drying: Touch dry: after 6 hours; Hard dry: after 24 hours

Viscosity: 165 KU ± 5 (23 ° C)

PH (25°C): 8 – 9

APPLICATION: The application surface should be free from all kinds of dust, rust, dirt, oil and old paint residues. A clean, dry and solid surface should be obtained by scraping the swollen, loosened and poured painted surfaces and applying Silkcoat Acrylic Primer after the surface cracks have been leveled with Silkcoat External Putty and smoothing. Elasticoat patterned is applied without thinning. Tools should be cleaned immediately after the application. For new coated surfaces, at least 28 days must be waited for the application of paint to the surface. The paint should be mixed until it is completely homogenous before use. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying. If applied on very bright and glassy surfaces, a solid surface should be formed by smoothing the surface first to ensure better adhesion.

CAUTION: -Avoid getting eye and skin contact. In case wash with plenty of water. -Preserve in a tightly closed container. -Keep above the reach of children -Do not dump into sewer system.

STORAGE: Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

PACKAGING: 25 Kg PE Bucket.