

## Hydroclean Plus

– Product Description: Pure acrylic binder based, silk matt appearance, flexible exterior paint.

### Features:

Hydroclean Plus paint is resistant to sunlight (UV), rain, snow and industrial effects. It has high covering and adhesion ability as well as can be easily applied. It does not crack due to its flexible structure.

### Application surfaces:

can be applied to all pre-prepared, clean and dry exterior surfaces.

### Technical Data:

Structure: Pure Acrylic

Consumption: Single Floor: 6- 10 (m<sup>2</sup> / lt)

Thinner: Water

Thinning Ratio: 40% max.

Drying Time: Touch 15 – 20 min; Dust Hold Time: 1 hour; Full Drying 24 hours

PH (25 ° C): 8 – 9

### Application:

The application surface should be free from all kinds of dust, rust, dirt, oil and old paint residues. A clean and dry surface must be obtained. If any cracks exist on the surface, they should be smoothed with Silkcoat External Putty, then Silkcoat Silicone Primer should be applied. Hydroclean Plus is applied in 2 coats with roller or brush by thinning with maximum 40% of clean water. Wait at least 2 hours between coats depending on the air temperature. Tools should be cleaned immediately after application. For new coated surfaces, at least 28 days must be waited for the application of paint to the surface. The paint should be mixed until it is completely homogenous before use. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying. If applied on very bright and glassy surfaces, a solid surface should be formed by smoothing the surface first to ensure better adhesion.

**Warning:**

S2: Keep out of the reach of children.

S24 / 25: Avoid contact with eyes and skin.

S46: If swallowed, seek medical advice immediately; Show the container or label.

Store the product in a tightly closed container.

Do not pour into the sewer.

**Storage:**

In a cool, clean and dry environment, the product can be stored for a minimum of 1 year without opening the door of the cabinet, without exposure to direct sunlight.

**Package:**

15 lt, PE bucket.