

Hydroclean

Product Description: Pure Acrylic binder based, silky matte exterior paint.

Features:

It is resistant to sun rays (UV), rain, snow and industrial effects. It has a high covering ability and is adhesive as well as can be easily applied.

Application surfaces:

can be applied to all pre-prepared, clean and dry exterior surfaces.

Technical Data:

Structure: Pure Acrylic

Consumption: Single Floor: 6- 10 (m² / lt)

Thinner: Water

Thinning Ratio: 10 – 15%

Density: 1,25 ± 0,05 (g / ml)

Drying Time: Touch 15 – 20 min; Dust Hold Time: 1 hour; Full Drying 24 hours

Viscosity: 120 KU ± 10 (23 ° C)

PH (25 ° C): 8 – 9

Brightness: Class G2

Dry Film Thickness: Class E2

Grain size: Class S1thin.

Water Steam Transfer Rate: Class V2

Water Transfer Speed: Class W3

Crack Covering Feature: Class A0

Carbon Dioxide Permeability: Class C0

Application:

The application surface should be free from all kinds of dust, rust, dirt, oil and old paint residues. A clean and dry surface must be obtained. If any cracks on the surface, they are to be smoothed with Silkcoat External Putty, then Silkcoat Acrylic Primer should be applied. Hydroclean is diluted with 10-15% clean water and applied in 2 coats with roller or brush. Wait at least 2 hours between coats depending on the air temperature. Tools should be cleaned immediately after application. For new coated surfaces, at least 28 days must be waited for the application of paint to the surface. The paint should be mixed until it is completely homogenous before use. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying. If applied on very bright and glassy surfaces, a solid surface should be formed by smoothing the surface first to ensure better adhesion.

Warning:

S2: Keep out of the reach of children.

S24 / 25: Avoid contact with eyes and skin.

S46: If swallowed, seek medical advice immediately; Show the container or label.

Store the product in a tightly closed container.

Do not pour into the sewer.

Storage:

In a cool, clean and dry environment, the product can be stored for a minimum of 1 year without opening the door of the cabinet, without exposure to direct sunlight.

Package:

15 lt, 2,5 lt PE bucket.

Quality certificates:

Found conform to TS 7847.