

İç Cephe Astarı

Product Description: Acrylic copolymer binder based, matt interior paint.

Features:Interior Primer, which is an interior wall paint that gives superior adhesion on new and old painted surfaces and can be easily applied without leaving traces, has high covering properties and water removal ability. Due to its water-based structure, there is no unpleasant odor, it can be inhaled.

Application surfaces:It can be applied to thin plaster, gross concrete, concrete plate, wood, gypsum plaster, gypsum plate and so on.

Technical Data:

Structure: Styrene Acrylic

Consumption: 10-15 (m² / lt), 65-100 (g / m²)

Thinner: Water

Thinning Ratio: 15-30%

Drying: Touch: 1-2 hours, Full: 4-5 hours.

Density: 1,62 ± 0,05 (g / ml)

Application:

A clean, dry and solid surface should be obtained after lightly smoothing the blistered and old painted surfaces. To obtain a smooth surface, gypsum or plastic paste is applied to the surface, then when it is dry it should be smoothed. Interior primer is diluted with 10-15% of water and applied as a single layer with brush or roller. For new coated surfaces, at least 28 days must be waited for the application of paint to the surface. The paint should be mixed until it is completely homogenous before use. The ambient and surface temperature should be between + 5°C and + 35°C during application and product drying. If applied on very bright and glassy surfaces, a solid surface should be formed by smoothing the surface first to ensure better adhesion.

Warning:

S2: Keep out of the reach of children.

S24 / 25: Avoid contact with eyes and skin.

S46: If swallowed, seek medical advice immediately; Show the container or label.

Store the product in a tightly closed container.

Do not pour into the sewer.

Storage:

At room temperature at least 1 year before opening.

Package:

20 kg, 3 kg PE bucket.