

Latex

DESCRIPTION: Acrylic copolymer binder based, matt appearance, economic interior paint.

CHARACTERISTIC:

- Breathable and adhesive
- High covering ability
- Easily applied without leaving traces
- Dries quickly
- Due to its water-based structure, it has no unpleasant odor
- Has water removal feature.

APPLICATION SURFACES:Can be applied on all kinds of prepared and clean surfaces.

TECHNICAL INFORMATION:

Structure: Styrene Acrylic

Consumption: 6 – 10 (m² / lt), 100-150 (g / m²)

Thinning ratio: 10-15%

Suitable primer: Silkcoat Universal primer, Silkcoat Izolac

Suitable paste: Silkcoat Acrylic Putty

Application tools: Brush, Roller.

Drying: Touch 15-20 min, hard dry for 2 hours.

Viscosity: 125 KU \pm 10 (23 ° C)

PH (25 ° C): 8 – 9

Density: 1,67 \pm 0,02 g / ml

Amount of solid matter: (64 \pm 2)%

Grain size: Class S1 (TS EN 13300)

Brightness: Class G2 (TS EN 13300)

Dry film thickness: (50 \pm 5) microns

Wet film thickness: (120 \pm 5) microns

APPLICATION:The application surface should be free from all kinds of dust, dirt and oil. The blistered and old painted surfaces are scraped, the surface defects and cracks are filled with suitable paste and smoothed for a clean, dry and solid surface to be obtained. Latex Plastic is applied 8-12 hours after having applied the primer to the prepared surface. Latex Plastic is diluted with 10-15% of clean water and applied in two layers by

roller, brush or spray method. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying.

CAUTION:

S2: Keep out of the reach of children.

S24 / 25: Avoid contact with eyes and skin.

S46: If swallowed, seek medical advice immediately; Show the container or label.

Store the product in a tightly closed container.

Do not pour into the sewer.

STORAGE:Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

PACKAGING:25 Kg, 17,5 Kg lt, 10Kg ,3 Kg PE Bucket