

Metalico

DESCRIPTION: Pure Acrylic binder based, psoriasis additive, pearl elegance decorative interior wall paint.

CHARACTERISTIC: Thanks to its pearl-like structure, Metalico offers a bright and special look like pearls, allowing for different pattern applications. It has a high degree of scraping ability. The water-based structure does not harm human health or the environment.

APPLICATION SURFACES: Can be applied on a wide range of interior old painted surfaces such as concrete, plaster, black plaster, betopan, glass textured and paintable wallpaper.

TECHNICAL INFORMATION

Structure: Pure Acrylic

Density: 1,04 ± 0,02 (gr / ml)

Consumption: 6 -8 m² / kg (Wood pattern and similar), 20- 30 m²/kg (Leopard pattern and similar), 125-170 (g/m²).

Thinner: Water

Thinning Ratio: %10 max.(with clean water)

Drying: Touch dry: after 15-20 minutes, Dust repulsive: after 1 hour, Hard dry: after 24 hours

APPLICATION: The application surface should be free from all kinds of dust, dirt and oil. A clean, dry and solid surface should be obtained after lightly smoothing the blistered and old painted surfaces. If the surface is not flat, a smooth surface should be obtained with Silkcoat Dahili Acrylic Paste for Metalico application. If the surface to be applied is flattened with gypsum plaster, Silkcoat İzolac should be used on the surface before Metalico application, Silkcoat Universal Primer should be used on smooth old painted surfaces, dirty or synthetic painted surfaces, and Silkcoat Putty Primer should be used on surfaces with putty application. After the primer application is dry, the floor is applied as two layers of Metalico. Wait at least 2 hours between coats. The Silkcoat Metalico is thinned with water according to the desired pattern and applied uniformly with the aid of a roller or brush. Metalico is applied up to 10 – 20 m² and is then given a special effect with hand tools (bumper, brush, spatula, chamois etc). In the same way, the other surfaces finish gradually. The spatula can work on top of different colors. Tools should be cleaned immediately after application. Metalico should be mixed until completely homogenous before use. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying. If applied on very bright and glassy surfaces, a solid surface should be formed by smoothing the surface first to ensure better adhesion.

CAUTION: -Avoid getting eye and skin contact. In case wash with plenty of water. -Preserve in a tightly closed container. -Keep above the reach of children -Do not dump into sewer system.

STORAGE: Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

PACKAGING: 10 kg, 3kg PE Bucket.