

## Platinum Plus İç Cephe

**DESCRIPTION:** Acrylic copolymer binder-based, water based, matt outward looks, silicone additives, first class, interior final coat paint.

**CHARACTERISTIC:** -Healthy and environmental friendly -Breathable -Easily applicable and leaves no remains. - High covering ability. -Easy cleanable through silicone -Silk-matt outward look, colourfast for years.

**APPLICATION:** After surface preparation, Platinum Interior Paint With Silicone can be applied on a wide range of interior surfaces such as old painted surfaces, concrete, plaster, rendering, cement board, wallpaper, glass textile etc.

### TECHNICAL INFORMATION:

Content: Styrene Acrylic

Consumption: Single coat: 13- 17 (m<sup>2</sup>/ lt), 85-130 (gr/m<sup>2</sup>)

Thinner: Water

Thinning Ratio: %10-15

Drying: Touch Dry: after 15-20 min, Dust repulsive: after 1 hour, Hard dry: after 24 hours

Viscosity: 125 KU ± 10 ( 23 ° C )

pH: 8 – 9 (25 ° C)

Density: 1,56 ± 0,02 (gr / ml)

Solids Content: %67±2

Thickness of dry coat: ( 30 ± 5 ) micron

Thickness of wet coat: ( 60 ± 5 ) micron

**SURFACE PREPARATION:** – The surface must be cleaned of any oil, dirt or dust. Swollen and old paintings must be scraped off. The surface must be clean, dry and solid. -Hollows and cracks should be filled with Interior Acrylic Putty in case of necessity.-After priming the surface with the appropriate primer, paint can be applied.

**APPLICATION:** -The paint should be thinned 10-15% with clean water and applied with roller, brush or spraying in two coats. -Leave 2 hours between coats depending on weather conditions.-After application tools should be cleaned with water.

**APPLICATION DETAILS:**-On new painted surfaces, make Sure that Surface has waited about 28 days before application. -Paint should be completely mixed so that it is homogenous. -Ambient and surface temperature should be between +5 and +35 degrees during the application and product drying season. -Gloss and glasslike Surfaces should be rubbed before application to obtain better adhesive and a healthy surface.

**CAUTION:** – S2: Keep out of the reach of children. – S24/25: Avoid getting eye and skin contact. In case wash with plenty of water. – S46: If swallowed, seek medical advice immediately and show this container or label. – Preserve in a tightly closed container. – Do not dump into the sewer system.

**STORAGE:** Keep at a cool and clean place away from sun light. It can be stored unopened 2 year at room temperature.

**PACKAGING:** 15 lt, 7,5 lt, 2,5 lt PE Bucket.