

## Silkoterasit Silikonlu

**DESCRIPTION:** Acrylic Copolymer binder based, grained exterior coating material.

**CHARACTERISTIC:** -High covering ability and feature of covering surface defects. -Breathable and water-based. -Resistant against external weather conditions. -Twisted and striped patterned decorative exterior ready plaster.

**APPLICATION SURFACES:** Can be applied on all exterior and interior prepared surfaces such as concrete , concrete plate ,cement and similar.

### TECHNICAL INFORMATION:

Structure: Styrene Acrylic

Consumption: 3000 – 3500 (g / m<sup>2</sup>)

Thinning ratio: Ready to use.

Density: 1,69 ± 0,2 (g / ml)

Suitable primer: Silkcoat Color Primer.

Application tools: Steel trowel (application), plastic trowel (pattern).

Drying: Touch 2-4 hours, hard dry 24 hours.

**APPLICATION:** The application surface should be free from all kinds of dust, rust, dirt, oil and old paint residues. Surfaces that are swollen, loosened and poured are scratched and the cracks on the surface are smoothed with Silkcoat External Putty. After the ground preparation is completed, Silkcoat Color Primer suitable for Silkoterasit is applied. After 1 day Silkoterasit can be applied.

**CAUTION:** -Avoid getting eye and skin contact. In case wash with plenty of water. -Preserve in a tightly closed container. -Keep above the reach of children -Do not dump into sewer system.

**STORAGE:** Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

**PACKAGING:** 25 Kg PE Bucket

**Poz No:** 04.470

