

## Stone

**DESCRIPTION:** Acrylic copolymer binder and granite marble-based, durable decorative exterior coating material.

**CHARACTERISTIC:** -Natural lively colourfast (preserves its natural color life for many years) -Resistant against atmospheric conditions. -Resistant against water ,washing and rubbing. -Breathable due to its water-based structure, a flexible wall covering and no unpleasant sent.

**APPLICATION SURFACES:** Silkcoat Stone can be easily applied on a wide range of interior and exterior surfaces, concrete, brick, plaster, concrete finishes, wood and similar surfaces except metal and glass.

### TECHNICAL INFORMATION:

Structure: Styrene Acrylic binder based thin / bold grained

Thinning Ratio: Thin / bold: Ready to use

Consumption: For thin: 2500-3500 (g / m2)

For bold: 4000-6000 (g / m2)

Density: For thin: 1,85 ± 0,2 (g / ml)

For bold: 1,80 ± 0,2 (g / ml)

**APPLICATION:** The application surface should be free from all kinds of dust, rust, dirt, oil and old paint residues. A clean, dry and solid surface should be obtained by scraping the swollen, loosened and poured painted surfaces and applying Silkcoat Acrylic Primer after the surface cracks have been leveled with Silkcoat External Putty and smoothing. Stone is poured into a large container. Depending on the ground and weather conditions, 1-1,5 lt of water is added and mixed. It is applied to the surface with the help of rectangular steel trowel. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying.

**CAUTION:** -Avoid getting eye and skin contact. In case wash with plenty of water. -Preserve in a tightly closed container. -Keep above the reach of children -Do not dump into sewer system.

**STORAGE:** Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

**PACKAGING:** 25 Kg PE Bucket

**Poz No:** 04.469