

## Velvetto

**Product Description:** The Velvetto Silkcoat Effects Group is a series of nacre-additives, velvet-patterned, glossy appearance, pure acrylic based, creating fun and moving spaces.

### Features:

Thanks to its nacre structure, Velvetto offers a semi-gloss and matte velvety special image like pearls, allowing for different pattern applications. Due to its water-based structure, it does not harm human health and environment.

### Scope of application:

All pre-painted surfaces can be applied to interior surfaces such as concrete, plaster, black plaster, betopan, glass textured and paintable wallpaper.

### Technical Data:

Density: 1,16 ± 0,02 (g / ml)

Consumption: 3,5-4 (m<sup>2</sup> / lt), 250-350 (g / m<sup>2</sup>)

Thinning ratio: Ready to use.

Drying Time: Touch 30-45 min; Dust repulsive 1 hour; Full drying 24 hours

### Surface Preparation:

- The application surface should be free from all kinds of dust, dirt and oil, old swollen paints should be thoroughly scraped, a clean dry and solid surface should be obtained.
- If the surface is not smooth, for Silkomat application, Silkcoat Internal Acrylic Putty should be applied in order to smoothen the surface.
- If the surface to be applied is flattened with gypsum plaster, Silkcoat İzolac should be used on the surface before Silkomat application, Silkcoat Universal Primer should be used on smooth, old painted surfaces, dirty or synthetic painted surfaces, and Silkcoat Putty Primer should be used on surfaces with Putty application.
- Silkomat of the same color is applied as a single layer with the primer.

## Application:

The application surface should be free from all kinds of dust, dirt and oil. A clean, dry and solid surface should be obtained after lightly sanding the blistered and old painted surfaces. If necessary, defects and cracks on the surface should be repaired with Silkcoat Internal Acrylic Putty. If the surface to be applied is flattened with gypsum plaster, Silkcoat İzolac should be used on the surface before Silkomatt application, Silkcoat Universal Primer on old painted, dirty or synthetic painted surfaces, Silkcoat Putty Primer should be used on surfaces with putty application. Silkomatt is applied as a single layer in the last layer of Velvetto. Velvetto is applied to the surface with the help of roller. The pattern is given to the product by circular movements with the help of special goods, without complete drying on the surface. The surface is left to dry for 4-6 hours depending on weather conditions. After the first layer application is applied, the second layer is applied with the help of Velvetto decorative trowel or roller to form a thin layer on the surface. After application, the surface is patterned with circular motions with the help of a special trowel. Tools should be cleaned immediately after application. The paint should be mixed until it becomes completely homogenous before use. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying. If applied on very bright and glassy surfaces, a solid surface should be formed by smoothing the surface first to ensure better adhesion.

## Warning:

S2: Keep out of the reach of children.

S24 / 25: Avoid contact with eyes and skin.

S46: If swallowed, seek medical advice immediately; Show the container or label.

Store the product in a tightly closed container.

Do not pour into the sewer.

## Storage:

In a cool, clean and dry environment, the product can be stored for a minimum of 1 year without opening the door of the cabinet, without exposure to direct sunlight.

## Package:

10 kg, 3 kg PE bucket.