

## Wood Protector

**Product Description:** Urethane Alkyd resin based, transparent wood protector effective against mold and mushroom.

### Features:

Wood Protector is a combination of both varnish and protector, thanks to its transparent structure, it colors without detracting from the natural appearance of the wood. Thanks to its antibacterial extracts, it prevents the formation of bacteria, fungi, molds and bedbugs on the wood. Protect the wood against UV rays. It is resistant to scratching and abrasion as well as the easy penetration to the surface.

### Application surfaces:

Can be applied to all interior and exterior wooden surfaces.

### Technical Data:

Structure: Urethane Alkyd resin based, transparent.

Consumption: 10-14 (m<sup>2</sup> / lt), 85-135 (g / m<sup>2</sup>)

Density: 0.92 ± 0.02 (g / ml)

Thinning ratio: 10-15%

Application tools: Brush, Roller, Pistole.

Drying: Dry in 6 – 12 hours depending on the type of wood.

Viscosity: 75 KU ± 10 (25 ° C)

Density: (0,92 ± 0,02) g / cm<sup>3</sup>

### Application:

All wood surfaces must be thoroughly smoothed to prepare a dry and clean surface with old paint and varnish free from oil, dirt and dust. Budaks should be burned and thoroughly cleaned with Cellulosic Thinner. Wood Protector is applied in 2 coats with 24 hours interval by brush, roller or spray method after thinning with 5% of thinner.

**Warning:**

S2: Keep out of the reach of children.

S24 / 25: Avoid contact with eyes and skin.

S46: If swallowed, seek medical advice immediately; Show the container or label.

Store the product in a tightly closed container.

Do not pour into the sewer.

Flash point 36 °C

Flammable, harmful when swallowed and breathed (inhaled).

**Storage:**

Storage life is at least 1 year in room conditions.

**Package:**

15 lt, 2,5 lt, 0.75 lt tin bucket.