

Viabella

PRODUCT DESCRIPTION: It is a new generation water-based, pure acrylic-based transformation paint with excellent adhesion to all surfaces.

FEATURES: It has very high covering power. It has excellent water resistance, therefore it also provides waterproofing on the surface it is applied to. It has high chemical resistance (soap, cleaning detergent, diluted bleach, etc.) Since it spreads very well, it does not leave roller or brush marks, allowing the user the desired time for the necessary corrections. Thanks to the shiny appearance it leaves after application, it does not require additional varnish application. It has high adhesion strength and does not require any primer. It is dirt and stain resistant and can be easily cleaned with a wet and soapy cloth. It does not have any disturbing odor. It is suitable for use indoors and outdoors.

APPLICATION AREAS: It can be applied to all kinds of surfaces such as wood, furniture, parquet, laminate, ceramic, porcelain, tile, marble, glass plastic, metal, aluminum, galvanized, zinc, stone, wall and paper.

TECHNICAL DATA:

DILUTION (by volume): Ready for use. Mix before application.

DRYING TIME (20°C): Dry to Touch; 1-2 hours, 24 hours to final drying. Applied surfaces should not be used for 1 day, and surfaces exposed to water should not be used for 2 days. Water accumulation should not be allowed for the first 7 days and it should be protected against impacts.

PAINTABLE AREA: With 1 liter, an area of 10-20m² can be painted in two coats, depending on the application method and the ground.

APPLICATION: The surface to be applied must be clean. The surface must be free from all factors that will reduce the adhesion of the paint to the surface, such as dust, dirt, oil and silicone, and sanding should be done when necessary. It does not require the use of any primer before application. It is recommended to prime metal surfaces with Silkcoat Anti-Rust to prevent corrosion. After opening the VIABELLA package, it is mixed until a homogeneous consistency is obtained. The product is applied to the pre-prepared surface in 2 layers without diluting, using a silk brush, velvet roller or spraying. At least 2 hours should be waited between coats. During application, care should be taken to keep the applied surface and ambient temperature between +5°C and +30°C.

WARNINGS: S2: Keep out of reach of children. S24/25: Avoid contact with eyes and skin. S46: If swallowed, seek medical advice immediately; Show the container or label. Store the product in a tightly closed container. Do not pour into drains.

STORAGE: 2 years in its original unopened package at room temperature.