

Marmarito Product Description: An acrylic copolymer-based decorative interior wall paint with a marble pattern.

Features: Marmarito, with its marble-like pattern and velvety texture, appeals to personal taste. In addition to having high coverage capacity, its flexible structure prevents cracking. The glossy surface it creates allows for high cleanability. Being water-based, it is harmless to both human health and the environment.

Application Areas: It can be applied to all previously painted surfaces, concrete, plaster, roughcast, betopan, glass fiber, and paintable wallpapers, provided the surface is properly prepared.

Technical Data:

- **Composition:** Styrene Acrylic
- **Consumption:** 4.5-5.5 (m²/l), 250-300 (g/m²)
- **Density:** 1.57 ± 0.02 (g/ml)
- **Solid Content:** 65% ± 2
- **Thinner:** Ready to use. Apply without thinning.
- **Drying Time:** Touch-dry in 30-45 minutes; dust-free in 1-1.5 hours; fully dry in 24 hours.

Application: The surface to be applied must be free from dust, dirt, and oil. Sand all blistered and old painted surfaces lightly to obtain a clean, dry, and solid surface. If the surface is uneven, Silkcoat Internal Acrylic Putty should be used to achieve a smooth surface before applying Marmarito. If the surface has been leveled with plaster, Silkcoat Izolac should be applied before using Marmarito. For smooth but old, dirty, or synthetic painted surfaces, apply Silkcoat Universal Primer. For putty-applied surfaces, use Silkcoat Putty Primer. Marmarito is applied in two coats using a trowel or spatula, without thinning. Wait at least 4 hours between coats depending on air temperature. After the second coat dries, for the final pattern, Marmarito is applied again with a spatula or trowel using cross-hatched and horizontal-vertical strokes. Excess paint is scraped off carefully to maintain the pattern, leaving a smooth surface. As a final step, polish the surface with circular and up-down motions while pressing on the trowel to smooth and shine it. Different colors can be layered on top of each other. Clean tools with water immediately after use. Mix thoroughly before use to achieve a homogeneous mixture. The ambient and surface temperature during application and drying should be between +5°C and +35°C. For very glossy and glassy surfaces, sand the surface first to ensure better adhesion.

Warnings:

- S2: Keep out of reach of children.
 - S24/25: Avoid contact with eyes and skin.
 - S46: If swallowed, consult a doctor immediately and show the container or label.
- Store the product in a tightly sealed container. Do not pour into drains.

Storage: Store in a cool, clean, and dry place, protected from direct sunlight. The product can be stored unopened for a minimum of 1 year. **Packaging:** 12 kg, 4 kg plastic buckets.