

Document type	Technical Data Sheet (TDS)
Name	Marmarito
Description	Acrylic Copolymer binder based, marble patterned decorative interior wall paint.
Characteristic	<ul style="list-style-type: none">-Harmless to people and environmental friendly through its water based content. -Suits your personal pleasure with its marble pattern, and velvety structure.-High covering ability.-Leaves no cracks.-Easy cleanable through glassy surface.
Application Surface	After surface preparation, marmarito can be applied o a wide range of interior surf- Aces such as old painted surfaces , concrete, plaster, rendering, cement board, wall- Paper glass textile etc.
Technical Information	Structure: Styrene Acrylic Consumption: 4,5- 5,5 (m ² / kg), 250-300 (g/m ²) Density: 1,57 ± 0,02 (g / ml) Solids Content: %65±2 Thinner: No thinning, ready to-use Drying: Touch dry: after 30-45 min, Dust repulsive: after 1-1.5 hour, Hard dry: after 24 hours
Surface Preparation	<ul style="list-style-type: none">– The surface must be cleared of any oil, dirt or dust. Swollen and old paintings must be scraped off. Surface must be clean, dry and solid. -In case that surface is not smooth, to be able to apply Marmarito on the surface first apply Silkcoat Dahili Akriklik Macun to obtain problem-free surface.-A smooth and glazed surfaces should be obtained by applying Silkoat Izolac before Marmarito application. smooth but old painted, sytnthetic and dirty surfaces should be obtained by applying Silkcoat Universal Primer. A surface which has been puttied should be obtained by applying Silkcoat Putty Primer. Silkcoat Universal Primer should be used on smooth, old painted surfaces, Silkcoat Universal Primer, Silkcoat Putty Primer should be used on surfaces that are applied with putty.
Application	<ul style="list-style-type: none">-Silkcoat Marmarito can be applied without diluting through spatula in two coats. - Leave minimum 4 hours between coats depending on weather conditions.-After 2. coat application is dry ,marmarito is applied with spatula without diluting again giving diagonal and vertical-horizontal non continous spatula or trowel strikes to make material textured on surface.– As a last step , the entire surface is shined by putting pressure on the trowel with up-down and right-left circular movements. Different colors can be obtained.–After application , tools should be cleaned with water.
Application Details	Before using Marmarito, it should be mixed until it becomes completely homogenous. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying. If applied on very bright and glassy surfaces, a solid surface should be formed by sanding the surface first to ensure better adhesion.
Cuation	<ul style="list-style-type: none">-Avoid getting eye and skin contact. In case wash with plenty of water.-Preserve in a tightly closed container.-Keep above the reach of children-Do not dump into sewer system.
Storage	Keep at a cool and clean place away from sun light. It can be stored unopened 2 year at room temperature.
Packaging	12kg, 4kg PE Bucket.