

Document type	Technical Data Sheet (TDS)
Name	Metalico Soft
Product Description	Pure Acrylic Emulsion binder based, psoriasis additives, nacre elegance decorative interior wall paint.
Features	Thanks to its nacre structure, Metalico Soft offers a bright and special look like pearl, allowing for different pattern applications. In addition to having a high covering ability, it also can be wiped. Due to its water-based structure, it does not harm human health or the environment.
Scope of application	All pre-painted surfaces can be applied to interior surfaces such as concrete, plaster, black plaster, betopan, glass textured and paintable wallpaper.
Technical Data	Structure: Pure Acrylic Density: 1,12 ± 0,02 (g / ml) Consumption: 10-16 (m ² / lt), 180-250 (g / m2) Thinning ratio: Ready to use. Drying Time: Touch 15 – 20 min; Dust repulsive 1 hour; Full drying 24 hours
Application	The application surface should be free from all kinds of dust, dirt and oil. A clean, dry and solid surface should be obtained after lightly smoothing the blistered and old painted surfaces. If necessary, defects and cracks on the surface should be repaired with Silkcoat Internal Acrylic Putty. If the surface to be applied is flattened with gypsum plaster, Silkcoat İzolac should be used on the surface before Metalico Soft application, Silkcoat Universal Primer should be used on old painted, dirty or synthetic painted surfaces and Silkcoat Paste Primer should be used on surfaces with putty application. In the last layer of the Metalico Soft color, Silkomatt is applied in one coat. After the primer is dry, Metalico Soft is diluted with 5% and applied with the help of roller or brush. After the first layer is dry, the second layer is applied with the help of a roller or brush. Patterns are given with special effect tools (bumper, brush, spatula, chamois) before the full drying takes place. Tools should be cleaned immediately after application. The paint should be mixed until it becomes completely homogenous before use. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying. If applied on very bright and glassy surfaces, a solid surface should be formed by smoothing the surface first to ensure better adhesion.
Warning	S2: Keep out of the reach of children. S24 / 25: Avoid contact with eyes and skin. S46: If swallowed, seek medical advice immediately; Show the container or label. Store the product in a tightly closed container. Do not pour into the sewer.
Storage	In a cool, clean and dry environment, the product can be stored for a minimum of 2 year without opening the door of the cabinet, without exposure to direct sunlight.
Package	10 kg, 3 kg PE bucket.