

Document type	Technical Data Sheet (TDS)
Name	Palace
Product Description	Pure Acrylic Emulsion Based, nacre additives, decorative interior wall paint grained structure with pearl effect.
Features	Thanks to its nacre structure, bright as pearl and matt, Palace offers a special image of texture, allowing for different pattern applications. Due to it being water-based sandy and having a metallic appearance, it gives the possibility to reflect your wall with coolness and splendor.
Application surfaces	All pre-painted surfaces can be applied to interior surfaces such as concrete, plaster, black plaster, betopan, glass textured and paintable wallpaper.
Technical Data	Density: 1,31 ± 0,02 (g / ml) Consumption: 3-4 (m ² / lt), 250-350 (g / m ²) Solid Matter: 60% ± 2 Thinning ratio: Ready to use. Drying Time: Touch 15 – 20 min; Dust retention 1 hour; Full drying 24 hours
Application	The application surface should be free from all kinds of dust, dirt and oil. A clean, dry and solid surface should be obtained after lightly smoothing the blistered and old painted surfaces. If necessary, defects and cracks on the surface should be repaired with Silkcoat Internal Acrylic Putty. If the surface to be applied is flattened with gypsum plaster, Silkcoat Izolac should be used on the surface before Silkcomatt application, Silkcoat Universal Primer on old painted, dirty or synthetic painted surfaces; Silkcoat Putty Primer should be used on surfaces with putty application. Silkcomatt is applied as a single layer in the final coat as the same color with Palace. Silkcoat Palace is applied, according to the desired pattern, with the help of a brush by taking a little amount of product with the brush's edge. When the product is about to dry, the liquid on the sand is removed with a clean, thick brush by slightly pressure. Thus, while the sand is taking its matte appearance, the subfloor will be gaining a glossy image. Tools should be cleaned immediately after application. The paint should be mixed until it is completely homogenous before use. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying. If applied on very bright and glassy surfaces, a solid surface should be formed by smoothing the surface first to ensure better adhesion.
Warning	S2: Keep out of the reach of children. S24 / 25: Avoid contact with eyes and skin. S46: If swallowed, seek medical advice immediately; Show the container or label. Store the product in a tightly closed container. Do not pour into the sewer.
Storage	In a cool, clean and dry environment, the product can be stored for a minimum of 2 year without opening the door of the cabinet, without exposure to direct sunlight.
Package	10 kg, 3 kg PE bucket.