

<b>Document type</b>	<b>Technical Data Sheet (TDS)</b>
<b>Name</b>	<b>Pearly</b>
<b>Description</b>	Pure Acrylic binder based, nacre additives, pearly-appearance, water-based, firstclass, decorative, final coat interior coating.
<b>Features</b>	Silkcoat Pearly, with a pearly texture, lined or curvy interior coating, has a high covering ability. In addition to being cleanable, it is water based and does not harm human health and environment.
<b>Application surfaces</b>	Can be applied to all pre-painted interior surfaces such as concrete, plaster, black plaster, betopan, glass textured and paintable wallpaper.
<b>Technical Data</b>	Structure: Pure Acrylic Consumption: Single coat: 2- 3 (m <sup>2</sup> / kg) Thinner: Water Solid Matter: 69% ± 2 Thinning Ratio: Applied without thinning. If necessary, max. 10% Drying Time: Touch, 25 – 30 min; Dust repulsive 1 hour; Full drying 24 hours PH (25 ° C): 8 – 9
<b>Application</b>	The application surface should be free from all kinds of dust, dirt and oil. A clean, dry and solid surface should be obtained after lightly smoothing the blistered and old painted surfaces. If necessary, defects and cracks on the surface should be repaired with Silkcoat Internal Acrylic Putty. Silkcoat Universal Primer should be used on new painted and absorbent surfaces, Silkcoat Paste Primer should be used on surfaces that are old painted, dirty or synthetic painted surfaces and putty applied surfaces. Silkcoat Pearl is applied on a single layer with glass trowel without being thinned. With the help of the glass trowel, the line or fold pattern is obtained. Application tools should be cleaned with water after application. For new coated surfaces, at least 28 days must be waited for the application of paint to the surface. The paint should be mixed until it is completely homogenous before use. The Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying. If applied on very bright and glassy surfaces, a solid surface should be formed by smoothing the surface first to ensure better adhesion.
<b>Warning</b>	S2: Keep out of the reach of children. S24 / 25: Avoid contact with eyes and skin. S46: If swallowed, seek medical advice immediately; Show the container or label. Store the product in a tightly closed container. Do not pour into the sewer.
<b>Storage</b>	In a cool, clean and dry environment, the product can be stored for a minimum of 2 year without opening the door of the cabinet, without exposure to direct sunlight.
<b>Package</b>	10 kg, 3 kg, 1 kg PE bucket.