

Document type	Technical Data Sheet (TDS)
Name	Prestige New
Product Description	Powder polymer-based, healthy, and decorative interior wall covering material.
Features	The Prestige Series Silk Plaster contributes to heat and sound insulation, is anti-static, and does not attract dust. In addition to being easy to apply, due to its water-based structure, it does not harm human health or the environment. It is odorless and breathable.
Application Areas	Silkcoat Silk Plaster fine plaster, gypsum plaster, drywall, wooden surfaces, and non-alkaline surfaces. It is not applicable to glass, brick, metal surfaces, exterior facades, and wet surfaces.
Technical Data	Structure: Powder polymer Consumption: 220-300 (g/m ²) Dilution Ratio: Ready for use Drying Time: 24 hours Application Thickness: 1 mm
Application	The surface to be applied must be free from dust, dirt, and oil. All raised and old painted surfaces should be lightly sanded, and a clean, dry, and solid surface should be obtained. For new plastered surfaces, Silkcoat Primer should be applied first. For old painted, dirty, or damp surfaces, any paint, dirt, soot, or similar residues should be thoroughly cleaned. After applying Silkcoat SX 2000 Gloss, Silkcoat Primer should be applied. Once the primer has dried, the silk plaster application can begin. The material in the bag should be poured into a container with approximately 6 liters of water and kneaded thoroughly. Depending on the climate and application conditions, additional water may be added if necessary. After the prepared material has rested for at least 20 minutes, it should be applied to the surface with a plastic trowel in a plastering technique, creating an average thickness of 1 mm. After application, tools should be cleaned immediately with water. In areas with excessive deformation, it is recommended to add one cup of Silkcoat SX 2000 Gloss to the material before kneading for each bag. During application, the surface should not be left unfinished. Application can be done with a plastic trowel or a spray gun. For newly plastered surfaces, it is recommended to wait at least 28 days before applying paint. During the application and drying process, the temperature of the environment and the surface should be between +5°C and +35°C.
Warning	Store the product in a tightly sealed container. Do not pour into drains.
Storage	The product can be stored for a minimum of 2 year in a cool, clean, dry environment, without direct sunlight, and with the container unopened.
Package	Bag.