

<b>Document type</b>	<b>Technical Data Sheet (TDS)</b>
<b>Name</b>	<b>Travertino</b>
<b>Description</b>	Acrylic copolymer cement based, antique stone decorative paint.
<b>Features</b>	Travertino, which offers a stone appearance, presents the quality of an aged, modern and live stone wall, also allows for different pattern applications. Because it is water-based, it does not harm human health and environment.
<b>Application surfaces</b>	All pre-painted surfaces with floor preparation can be applied to interior surfaces such as concrete, plaster, black plaster, betopan.
<b>Technical Data</b>	Structure: Styrene Acrylic Consumption: 1-1,5 m <sup>2</sup> / lt, 1500-2500 (g / m <sup>2</sup> ) Density: 1.95 ± 0.02 (g / ml) Thinning ratio: Ready to use. Drying Time: It takes 1 day to hard dry. If applied in 2 coats, the first coat dries in 24 hours.
<b>Application</b>	The application surface should be free from all kinds of dust, dirt and oil. A clean, dry and solid surface should be obtained after lightly smoothing the blistered and old painted surfaces. If necessary, defects and cracks on the surface should be repaired with Silkcoat Internal Acrylic Putty. Travertino is mixed with 20-25% water until the first layer is flattened and mixed until it becomes homogenous. Travertino is applied to the entire surface with trowel. To make the surface smooth, the first coat is left to dry for 1 day after it has been smoothed with a trowel. Prior to the application of the second layer, the surface is soaked with a roll of water. When the dry surface is obtained, the second layer is again applied to the surface with a trowel. When the second coat surface is about to dry, the patterns are created with the help of the backside of the trowel. After enough lines have been formed, they are again smoothed with the trowel and left to dry for another day. On the third day, The final surface is again wetted with water by means of a roller. Without full drying, Silkcoat Artec, which is the last layer, is diluted with 25-30% and applied with the help of a special tool. Travertino should be mixed until completely homogenous before use. Dilute Travertino as much as you can on each floor. Since the product is cement based, it can be dried. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying. If applied on very bright and glassy surfaces, a solid surface should be formed by smoothing the surface first to ensure better adhesion.
<b>Warning</b>	S2: Keep out of the reach of children. S24 / 25: Avoid contact with eyes and skin. S46: If swallowed, seek medical advice immediately; Show the container or label. Store the product in a tightly closed container. Do not pour into the sewer.
<b>Storage</b>	In a cool, clean and dry environment, the product can be stored for a minimum of 2 year without opening the door of the cabinet, without exposure to direct sunlight.
<b>Package</b>	25 kg, 15 kg PE bucket.