

Document type	Technical Data Sheet (TDS)
Name	Velvetto Soft
Product Description	The Velvetto Soft Silkcoat Effects Group is a series of psoriasis-added, velvet-patterned, shiny appearance, pure acrylic-based, creating fun and moving spaces.
Features	Velvetto Soft, which allows different pattern applications, offers a nacre semi-gloss and matt-like pearl special appearance. Due to its water-based structure, it does not harm human health or the environment.
Application surfaces	All pre-painted surfaces can be applied to interior surfaces such as concrete, plaster, black plaster, betopan, glass textured and paintable wallpaper.
Technical Data	Density: 1,13 ± 0,02 (g / ml) Consumption: 3,5-4 (m ² / lt), 250-350 (g / m2) Thinning ratio: Ready to use. Drying Time: Touch 30-45 min; Dust repulsive 1 hour; Full drying 24 hours
Application	The application surface should be free from all kinds of dust, dirt and oil. A clean, dry and solid surface should be obtained after lightly smoothing the blistered and old painted surfaces. If necessary, defects and cracks on the surface should be repaired with Silkcoat Internal Acrylic Putty. If the surface to be applied is flattened with gypsum plaster, Silkcoat İzolac should be used on the surface before Silkomatt application, Silkcoat Universal Primer on old painted, dirty or synthetic painted surfaces, Silkcoat Putty Primer should be used on surfaces with putty application. Silkomatt is applied as a single layer on the last layer of the same color of Velvetto Soft. Velvetto is applied to the surface with the help of roller. The pattern is given to the product by circular movements with the help of a special trowel, without complete drying on the surface. The surface is left to dry for 4-6 hours depending on weather conditions. After the first layer application is applied, the second layer is applied with the help of a Velvetto decorative trowel or roller to form a thin layer on the surface. After application, the surface is patterned with circular motions with the help of special trowel. Tools should be cleaned immediately after application. The paint should be mixed until it becomes completely homogenous before use. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying. If applied on very bright and glassy surfaces, a solid surface should be formed by smoothing the surface first to ensure better adhesion.
Warning	S2: Keep out of the reach of children. S24 / 25: Avoid contact with eyes and skin. S46: If swallowed, seek medical advice immediately; Show the container or label. Store the product in a tightly closed container. Do not pour into the sewer.
Storage	In a cool, clean and dry environment, the product can be stored for a minimum of 2 year without opening the door of the cabinet, without exposure to direct sunlight.
Package	10 kg, 3 kg plastic bucket.