

SILKCOAT®

'art of paint'



Technical Data Sheet (TDS)

Product Name: Acrylic Putty (Interior)

Product Description: Interior wall putty based on an acrylic copolymer binder.

Features: Thanks to its special formulation, it is resistant to external atmospheric conditions. It fills plaster defects and is easy to apply. Offers minimum consumption, breathability, and fast drying. Its flexibility allows it to bridge cracks and prevents them from reaching the final topcoat.

Application Areas: Can be applied to traditional plaster, concrete, asbestos boards, aerated concrete, and similar surfaces.

Technical Data: Binder Type: Styrene acrylic Consumption: 500 – 1500 g/m² depending on surface condition Thinning Ratio: Not diluted, ready to use Application Tools: Trowel, spatula Drying Time: 1 – 4 hours depending on weather conditions pH: 8 – 9 Density: 1.88 ± 0.05 g/ml Solid Content: 73% ± 5 Dry Film Thickness: 350 ± 50 microns Wet Film Thickness: 650 ± 50 microns.

Application: Should be applied without thinning on both old and new surfaces. For concrete surfaces, Acrylic Putty should be mixed with 20% cement to obtain a smooth and solid surface. During application and drying, ambient and surface temperatures should be between +5°C and +30°C.

Warnings: S2: Keep out of reach of children. S24/25: Avoid contact with eyes and skin. S46: If swallowed, seek medical advice immediately and show the container or label. Store in a tightly closed container. Do not dispose of into drains.

Storage: Can be stored for a minimum of 2 years in a cool, clean, and dry environment, protected from direct sunlight, provided the container remains unopened.

Packaging: 15 L, 7.5 L, 2.5 L plastic buckets.



www.silkcoat.com
info@silkcoat.com



0(212)789 56 43



Kaleiçi Mah. Gökçeali Cad.
No: 63 Çatalca, İstanbul, Türkiye